



Unit:mm



	$V_{DRM}$	$V_{DSM}$
	V	V
<b>BTA41-200</b>	200	220
<b>BTA41-400</b>	400	450
<b>BTA41-600</b>	600	700
<b>BTA41-800</b>	800	900
<b>BTA41-1000</b>	1000	1100
<b>BTA41-1200</b>	1200	1300



Dim.	Inches		Millimeter	
	min	max	min	max
A	0.81	0.835	20.57	21.21
B	0.61	0.63	15.49	16
C	0.178	0.188	4.52	4.78
D	0.055	0.07	1.4	1.78
E	0.487	0.497	12.37	12.62
F	0.635	0.655	16.13	16.64
G	0.022	0.029	0.56	0.74
H	0.075	0.095	1.91	2.41
J	0.575	0.625	14.61	15.88
K	0.211	0.219	5.36	5.56
L	0.422	0.437	10.72	11.1
M	0.058	0.068	1.47	1.72
N	0.045	0.055	1.14	1.4
P	0.095	0.115	2.41	2.92
O	0.008	0.016	0.2	0.41
R	0.008	0.016	0.2	0.41
U	0.159	0.163	4.04	4.14
W	0.085	0.095	2.17	2.42

Symbol	Test Conditions	Maximum Ratings	Unit
$I_{TRMS}$	$T_{VJ}=80^{\circ}C$	41	A
$I_{TSM}$	$T_{VJ}=45^{\circ}C$ $V_R=0$ $t=10ms$ (50Hz), sine $t=8.3ms$ (60Hz), sine	420 400	A
	$T_{VJ}=T_{VJM}$ $V_R=0$ $t=10ms$ (50Hz), sine $t=8.3ms$ (60Hz), sine	350 320	
$i^2t$	$T_{VJ}=45^{\circ}C$ $V_R=0$ $t=10ms$ (50Hz), sine $t=8.3ms$ (60Hz), sine	880 850	$A^2s$
	$T_{VJ}=T_{VJM}$ $V_R=0$ $t=10ms$ (50Hz), sine $t=8.3ms$ (60Hz), sine	760 720	
$(di/dt)_{cr}$	$T_{VJ}=T_{VJM}$ $f=50Hz$ , $t_p=200us$ $V_D=2/3V_{DRM}$ $I_G=0.3A$ $di_G/dt=0.3A/us$ repetitive, $I_T=40A$	50	A/us
	non repetitive, $I_T=I_{TAVM}$	300	
$(dv/dt)_{cr}$	$T_{VJ}=T_{VJM}$ ; $R_{GK}=\infty$ ; method 1 (linear voltage rise) $V_{DR}=2/3V_{DRM}$	500	V/us
$P_{GM}$	$T_{VJ}=T_{VJM}$ $I_T=I_{TAVM}$ $t_p=30us$	10	W
	$t_p=300us$	5	
$P_{GAV}$		1	W
$V_{RGM}$		10	V
$T_{VJ}$ $T_{VJM}$ $T_{stg}$		-40...+125 125 -40...+125	$^{\circ}C$
$V_{ISOL}$	50/60Hz, RMS $t=1$ minute, leads-to-tab	2500	V~
$M_d$	Mounting torque (M4)	0.8...1.5	Nm
Weight		6	g

Symbol	Test Conditions		Characteristic Values	Unit
$I_R, I_D$	$T_{VJ}=T_{VJM}; V_D=V_{DRM}$		10	mA
$V_{TM}$	$I_T=41A; T_{VJ}=25^{\circ}C$		1.44	V
$V_{TO}$	For power-loss calculations only ( $T_{VJ}=125^{\circ}C$ )		0.85	V
$r_T$			10	$m\Omega$
$V_{GT}$	I	$V_D=6V; I_T=1A; T_{VJ}=25^{\circ}C$	1.3	V
	II		1.3	
	III		1.3	
	IV		1.5	
$I_{GT}$	I	$V_D=6V; I_T=1A; T_{VJ}=25^{\circ}C$	50	mA
	II		50	
	III		50	
	IV		100	
$V_{GD}$	$T_{VJ}=T_{VJM};$	$V_D=2/3V_{DRM}$	0.2	V
$I_{GD}$			10	mA
$I_H$	$T_{VJ}=25^{\circ}C; V_D=6V; R_{GK}=\infty$		100	mA
$R_{thJC}$	DC current		1.3	K/W
$R_{thJH}$	DC current		1.5	K/W
$a$	Max. acceleration, 50 Hz		50	$m/s^2$

Fig. 1: Maximum power dissipation versus RMS on-state current (full cycle).




Fig. 3: Relative variation of thermal impedance versus pulse duration.




Fig. 5: Surge peak on-state current versus number of cycles.




Fig. 2: RMS on-state current versus case temperature (full cycle).




Fig. 4: On-state characteristics (maximum values).




Fig. 6: Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10$  ms, and corresponding value of  $I^2t$ .




Fig. 7: Relative variation of gate trigger current, holding current and latching current versus junction temperature (typical values).




Fig. 8: Relative variation of critical rate of decrease of main current versus (dV/dt)<sub>c</sub> (typical values).





Fig. 9: Relative variation of critical rate of decrease of main current versus junction temperature.



Symbol	Test Conditions		Characteristic Values	Unit
$I_R, I_D$	$T_{VJ}=T_{VJM}; V_D=V_{DRM}$		10	mA
$V_{TM}$	$I_T=41A; T_{VJ}=25^{\circ}C$		1.44	V
$V_{TO}$	For power-loss calculations only ( $T_{VJ}=125^{\circ}C$ )		0.85	V
$r_T$			10	$m\Omega$
$V_{GT}$	I	$V_D=6V; I_T=1A; T_{VJ}=25^{\circ}C$	1.3	V
	II		1.3	
	III		1.3	
	IV		1.5	
$I_{GT}$	I	$V_D=6V; I_T=1A; T_{VJ}=25^{\circ}C$	50	mA
	II		50	
	III		50	
	IV		100	
$V_{GD}$	$T_{VJ}=T_{VJM};$	$V_D=2/3V_{DRM}$	0.2	V
$I_{GD}$			10	mA
$I_H$	$T_{VJ}=25^{\circ}C; V_D=6V; R_{GK}=\infty$		100	mA
$R_{thJC}$	DC current		1.3	K/W
$R_{thJH}$	DC current		1.5	K/W
$a$	Max. acceleration, 50 Hz		50	$m/s^2$